PNG-GROUP-DRAFT
PNG-Proposals
Expires: 14 Mar 1997

PNG Development Group
png-list@dworkin.wustl.edu
14 Sep 1996

PNG Proposed Chunks, draft 19960914

File

png-proposed-chunks-19960914.txt

Status of this Memo

This document is an informal draft of the PNG development group.

Comments on this document can be sent to the PNG specification maintainers at `png-info@uunet.uu.net` or at `png-list@dworkin.wustl.edu`.

Distribution of this memo is unlimited.

At present, the latest version of this document is available on the World Wide Web from `ftp://swrinde.nde.swri.edu/pub/png-group/documents/`.

Notices

Copyright © 1996 Thomas Boutell

Permission is granted to copy and distribute this document for any purpose and without charge, provided that the copyright notice and this notice are preserved, and that any substantive changes or deletions from the original are clearly marked.

Abstract

This document describes some special-purpose chunk types that have been proposed for use in various PNG (Portable Network Graphics) applications. They have not yet been approved for registration by the PNG developers, and therefore are experimental and their format is subject to change. The proposed chunks are `alIG`, `fiNG`, `spAL`, and `srGB`.

Contents

1 Introduction 2
2 Using Proposed PNG Chunks 2
3 Summary of Proposed Chunks 2
4 Proposed Chunk Specifications 3
4.1 alIG Alignment 3
4.2 fiNG Fingerprint 4
4.3 spAL Suggested Palette 5
4.4 srGB Standard RGB profile 6
5 Chunks not described here 7
6 Security considerations 7
7 References 8
8 Credits 8

1 Introduction

Chunks described here have been proposed to the PNG development group. Their definitions are subject to change until such time as the group formally registers them. No decoder is required or expected to implement these chunks except for experimental or evaluation purposes. Comments on these proposals, and new proposals for additional chunk types, should be sent to the PNG specification maintainers at `png-info@uunet.uu.net`. The basic PNG specification is available from the W3C archive at `http://www.w3.org/pub/WWW/TR/WD-png`.

2 Using Proposed PNG Chunks

No chunks described in this document have yet been registered by the PNG maintainers. Therefore they have a lower-case letter in the second position of the chunkname. They are **experimental** chunks and the format is subject to change. If and when any become registered, the second letter of the chunk name will become uppercase, the "signature" field, if present, and its zero-byte terminator will be deleted. The chunk description will be moved either to a PNG extensions document or to the core PNG specification. There will be no further change to the format.

Whenever you use any of these unregistered chunks you should also include a `tEXt` chunk describing it, for example:

```
tEXtComment\0
This file contains a spAL chunk written according to
the format given in Version 19960914 of the PNG Proposed
Chunks document.
```

For those proposed chunks that have a "signature" field, decoders should check to ensure that the signature field is present and that its contents exactly match the specified string.

3 Summary of Proposed Chunks

This table summarizes some properties of the proposed chunks described in this document.

Chunk name	Multiple OK?	Ordering constraints
alIG	No	Before IDAT
fiNG	No	None
spAL	Yes	Before IDAT
srGB	No	Before IDAT

4 Proposed Chunk Specifications

This section provides the detailed specifications for the proposed chunks.

4.1 `alIG` Alignment

This chunk can be used to provide alignment information to applications. It is especially useful for transparent images in which the edges of the interesting part of the picture do not correspond exactly to the edges of the image data. It can be helpful in aligning the picture with adjacent text, if there is a specific location in the picture that should be aligned with the text baseline. (We use "picture" to mean the thing depicted, as opposed to "image" which is the entire width x height rectangle described by the PNG stream.)

The format of this chunk has not changed since version 19960406 of this document.

This chunk's contents are

left	4 bytes	left side of picture
center	4 bytes	center of picture (horizontal)
right	4 bytes	right side of picture
top	4 bytes	top of picture
middle	4 bytes	middle of picture (vertical)
baseline	4 bytes	typographic baseline of picture (vertical)
bottom	4 bytes	bottom of picture

All values are signed 32-bit integer values, measured in pixels downward from the top of the image or rightward from the left edge of the image.

Applications will not normally try to use all of the alignment values at once. A browser might use the "center" value when it wishes to center the image left-to-right on a page. A typographic system might use the "top" value to line up an image that contains a fancy capital letter with the top of the adjacent text, or the "baseline" value to line up images containing mathematical equations. Typographic systems could also determine the typographic "height", "depth", "width", and reference point values:

```
font_height := baseline - top
font_width  := right - left
font_depth  := bottom - baseline
font_ref_x  := left
font_ref_y  := baseline
```

If the `alIG` chunk is not present, applications can assume the following values:

```
left        := 0
center      := width/2
right       := width
top         := 0
middle      := height/2
baseline    := height
bottom      := height
```

If an encoder writes the `alIG` chunk, it must supply all of the fields, and should use these values as defaults.

Only one `alIG` chunk is permitted in a PNG datastream. If present, it must appear prior to the first `IDAT` chunk.

4.2 `fiNG` Fingerprint

This chunk contains an MD5 fingerprint of the uncompressed, unfiltered, uninterlaced image data, that can be used for rapidly determining whether two files contain the same image, without having to actually decode the IDAT chunks.

The MD5 fingerprint is calculated according to the RSA Data Security, Inc. MD5 Message-Digest Algorithm, copyright by RDS Data Security, Inc., 1991-1992. A reference implementation of the algorithm and the license for its use are given in [MD5].

The format of this chunk has not changed since version 19960710 of this document.

The `fiNG` chunk's contents are

```
16 bytes: image fingerprint
```

The fingerprint is the MD5 digest value computed on the image data, promoted by left-bit-replication (see bit_depth scaling in PNG spec) to 16-bit RGBA (colortype 6). Scaling is done without regard to the `sBIT`

chunk, if present. When promoting truecolor images, fill the alpha samples with 0xffff (all ones). The fingerprint is calculated without regard to any ancillary chunks. The value is computed on the data in the same order as the bytes would appear in a color type 6 datastream, except that no filter bytes are included in the calculation. The MD5 fingerprint value is computed as described in RFC 1321 [RFC1321].

An image's fingerprint will not change if the image is changed from interlaced to noninterlaced, or compressed with a different method, or filtered differently, or if any ancillary chunks are added, modified, or removed. It will change if there is any lossy conversion of the pixel data or if the PLTE data is changed in an indexed-color image.

The `fiNG` fingerprint is trivial to forge. Be cautious when using a fingerprint chunk generated by someone else. It is safer to recalculate and install your own `fiNG` chunk when you receive an image from outside of your control.

While the `fiNG` chunk does not have any ordering requirements, you should put it early in the file for quick access.

4.3 `spAL` Suggested Palette

This chunk can be used to suggest a reduced palette to be used when the display device is not capable of displaying the full range of colors present in the image. If present, it provides a recommended set of colors, with alpha and frequency information, that can be used to construct a reduced palette to which the truecolor image can be quantized.

The format of this chunk has not changed since version 19960914 of this document. In the previous version it was called `spLT` and the name has been changed to avoid confusion. It is intended to register the chunk as `sPLT`. The "signature" field and its null separator will not be included in the registered chunk.

This chunk's contents are a zero-byte-terminated text string that names the palette, a zero-byte-terminated signature to identify the version, followed by a 4-byte gamma value, followed by a series of palette entries, each a ten-byte series, containing five unsigned integers:

```
n bytes:  (ASCII text) palette name
1 byte:   (null) terminator

20 bytes: signature ("PNG group 1996-09-14")
1 byte:   (null) separator

4 bytes:  (unsigned integer) gamma
```

```
2 bytes:  (unsigned integer)  red intensity
          0:   black
          etc.
          65535: full red intensity
2 bytes:  (unsigned integer)  green intensity
2 bytes:  (unsigned integer)  blue intensity
2 bytes:  (unsigned integer)  alpha
          0: fully transparent
          etc.
          65535: fully opaque
2 bytes:  (unsigned integer)  frequency
          (relative frequency of occurrence)
etc.
```

There can be any number of entries; a decoder determines the number of entries from the remaining chunk length after the gamma field. This length not divisible by ten is an error. Entries must appear in decreasing order of "frequency".

The "name" (e.g. "rgba512 8-8-4-2 color cube", "rgb256 winter scenery", "rgb242 6-6-6 color cube plus 26 gray levels", "Windows white background", "Browser Safe Palette", "Sepia") identifies the palette, which can permit applications or people to choose the appropriate one when more than one suggested palette appears in a PNG file. The "name" string must follow the format of a `tEXt` keyword: It must consist only of printable ASCII characters and must not have leading or trailing blanks, but can have single embedded blanks. There must be at least one and no more than 79 characters in the name. Names are case-sensitive.

The gamma field gives the value of gamma, times 100000, that is associated with the palette entries.

The red, green, and blue values are not premultiplied by alpha, nor are they precomposited against any background. A decoder can build a palette by compositing those palette entries against any background color or set of background colors that it chooses. See [link to bKGD]

Each frequency entry is proportional to the fraction of pixels in the image that are closest to that palette entry, without regard to any compositing against a background palette. The exact scale factor is chosen by the encoder, but should be chosen so that the range of individual values reasonably fills the range 0 to 65535. It is acceptable to artificially inflate the "frequency" values for "important" colors such as those in a company logo or in the facial features of a portrait. Zero is a valid value for frequency, meaning the color is "least important" or that it is rarely if ever used.

The palette uses 16 bits (2 bytes) per value regardless of the image bit depth specification. Decoders wishing to construct a palette with a smaller bit depth can accomplish this by scaling down the RGB entries, as described under "bit depth rescaling" in the PNG specification.

Note: Earlier versions of the PNG specification recommended that the `PLTE` [link to PLTE] and `hIST` chunks be used for this purpose. While this is still allowed, to maintain backward compatibility, the `spAL` chunk is preferable, particularly when transparent pixels are present. When both the `PLTE` and `spAL` chunks are present, the `PLTE` data should only be used for decoding the indexed-color (color type 3) pixels, and the

spAL data should be used for constructing the display palette. If the hIST chunk is also present, decoders that process the spAL chunk should ignore it.

This chunk can appear for any color type. If this chunk does appear, it must precede the first IDAT chunk. There can be multiple spAL chunks, with different names.

4.4 srGB Standard RGB profile

If the srGB chunk is present, the image conforms to the International Color Commission's sRGB profile, and should be displayed using the specified rendering intent.

The format of this chunk has not changed since version 19960914 of this document. The "signature" field and its null separator will not be included in the registered chunk.

An srGB chunk contains:

```
20 bytes: signature ("PNG group 1996-09-14")

1 byte: null separator

1 byte: Rendering intent
        0: Perceptual rendering intent
        1: Relative colorimetric rendering intent
        2: Saturation preserving rendering intent
        3: Absolute colorimetric rendering intent
```

If the srGB chunk is present, the image conforms to the transfer characteristic, chromaticities, illuminant, viewing flare, ambient illumination, and other properties as specified by the International Color Consortium [ICC] sRGB named profile described in [STOKES]. This means that the image was written by an ICC-aware application and if displayed by an ICC-aware application using the specified rendering intent will achieve near-optimum rendering within the physical limitations of the output device.

If this chunk is used, the gAMA and cHRM chunks should also be present for compatibility with non-ICC-aware applications and should contain the following values:

```
gAMA:
   Image gamma:   45000
```

```
cHRM:
   White Point x: 31270
   White Point y: 32900
   Red x:         64000
   Red y:         33000
   Green x:       30000
   Green y:       60000
   Blue x:        15000
   Blue y:        06000
```

5 Chunks not described here

Additional chunks have been proposed for scientific visualization purposes. Since they are not expected to be implemented by general-purpose decoders, the are described separately in the PNG Scientific Visualization Chunks document [SCIVIS]. The proposed chunks described there are drNG/DrNG, faLT, loGE/LoGE, pCAL, tsCL, xsCL, ysCL, and zsCA.

6 Security considerations

Security considerations are addressed in the basic PNG specification, http://www.w3.org/pub/WWW/TR/WD-png.

The same precautions taken when displaying tEXt data should be taken when displaying the text contained in the "name" strings of the spAL chunk. Viewers should not display these strings directly without first checking for the presence of nonprintable characters, and for the <ESC> character in particular.

The fiNG fingerprint is trivial to forge. Be cautious when using a fingerprint chunk generated by someone else.

No known additional security hazards are posed by the chunks described here.

7 References

[MD5]

RFC 1321, The MD5 Message-Digest Algorithm.

[STOKES]

http://www.hpl.hp.com/personal/Michael_Stokes/srgb.htm .

[SCIVIS]

PNG Scientific Visualization Chunks, available at ftp://swrinde.nde.swri.edu/png-group/documents/

8 Credits

Trademarks

- Windows is a trademark of MicroSoft Corp.

Contributors

Contributors' names are presented in alphabetical order:

- Mark Adler, madler@alumni.caltech.edu
- Thomas Boutell, boutell@boutell.com
- Christian Brunschen, cb@df.lth.se
- Adam M. Costello, amc@cs.berkeley.edu
- Lee Daniel Crocker, lee@piclab.com
- Andreas Dilger, adilger@enel.ucalgary.ca
- Oliver Fromme, fromme@rz.tu-clausthal.de
- Todd French, tfrench@sandia.gov
- Jean-loup Gailly, gzip@prep.ai.mit.edu
- Chris Herborth, chrish@qnx.com
- Alex Jakulin, alex@hermes.si
- Neal Kettler, kettler@cs.colostate.edu
- Jim King, jimk@mathtype.com
- Tom Lane, tgl@sss.pgh.pa.us
- Alexander Lehmann, alex@hal.rhein-main.de
- Chris Lilley, chris@w3.org
- Dave Martindale, davem@cs.ubc.ca
- Owen Mortensen, ojm@csi.compuserve.com
- Robert P. Poole, lionboy@primenet.com
- Glenn Randers-Pehrson, glennrp@arl.mil or randeg@alumni.rpi.edu
- Greg Roelofs, newt@pobox.com
- Willem van Schaik, gwillem@ntuvax.ntu.ac.sg

- Guy Schalnat
- Paul Schmidt, pschmidt@photodex.com
- Tim Wegner, 71320.675@compuserve.com

Editor

- Glenn Randers-Pehrson, glennrp@arl.mil or randeg@alumni.rpi.edu

End of PNG Proposed Chunks Listing. Expires 14 Mar 1997.