

List1

	IM	GM	Images	
3FR		R^		
8BIM		RW		
8BIMTEXT		RW		
AAI	RW	RW	RW	
APNG	RW			
APP1JPEG		RW		
ART	RW	RW	RW	
ARW	R	R^		
AVI	R			
AVIF	RW	R		
AVS	RW	RW	RW	
B		RW		
BAYER	RW			
BIE		RW^		
BIGTIFF		RW^		
BPG	RW			
BMP, BMP2, I	RW	RW	RW	
BRF	W	W^		
CALS	R	R		
CGM		R		
CIN	RW	R		
CIP	W			

List1

CMYK	RW	RW	
CMYKA	RW		
CR2	R	R [^]	
CRW	R	R [^]	
CUBE	R	RW	
CUR	R	R	
CUT	R	R	R
DCM	R	R	
DCR	R	R	
DCX	RW	RW	
DDS	RW		
DEBUG	W		
DIB	RW	RW	RW
DJVU	R		
DMR	RW		
DNG	R	R [^]	
DOT	R	RW	
DPX	RW	RW	
EMF	R	R	

List1

EPDF	RW	RW		
EPI	RW	RW		
EPS	RW	RW	RW	
EPS2	W	W		
EPS3	W	W		
EPSF	RW	RW		
EPSI	RW	RW		
EPT	RW	RW		
ERF		R^		
EXR	RW			
FARBFELD	RW			
FAX	RW	RW		
FIG		R		
FITS	RW	RW	RW	
FL32	RW			
FLIF	RW			
FPX	RW	RW		
FTXT	RW			
GIF	RW	RW		
GPLT	R		RW	
GRAY	RW	RW		

List1

GRAYA	RW	RW	
HDR	RW		
HEIC	RW	R [^]	
HEIF		R	
HPGL	R	R	
HRZ	RW	RW	R
HTML	RW	RW	
ICO	R	R	RW
INFO	W		
ISOBRL	W		
ISOBRL6	W		
JBIG	RW	RW	
JNG	RW	RW	
JP2	RW	RW	
JPT	RW		
J2C	RW		
J2K	RW		
JPEG	RW	RW	RW
JXR	RW		

List1

JSON	W	RW	
JXL	RW	RW	
K25		R	
KDC		R	
KERNEL	W	RW	
MAN	R	R	
MAT	R	RW	RW
MEF		R	
MIFF	RW	RW	
MONO	RW	RW	
MNG	RW	RW	
M2V	RW	RW	
MPEG	RW	RW	
MPC	RW	RW	
MPO	R	RW	
MPR	RW	RW^	

List1

MRW	R	R		
MSL	RW	RW		
MTV	Rw	Rw		
MVG	RW	RW		
NEF	R	R		
OKO			RW	
ORF	R	R		
ORA	R	R		
OTB	RW	RW		
P7	RW	RW		
PALM	RW	RW		
PAM	W	RW		
CLIPBOARD	RW	RW		
PBM	RW	RW		
PCD	Rw	Rw		
PCDS	Rw	Rw		
PCL	W	W		
PCX	Rw	Rw	Rw	
PDB	RW	RW		

List1

PDF	RW	RW	
PEF	R	R	
PES	R		
PFA	R	R	
PFB	R	R	
PFM	RW		
PGM	RW	RW	
PHM	RW		
PICON	RW	RW	
PICT	RW	RW	
PIX	R	R	
PNG	RW	RW	RW
PNG8	RW	RW	

List1

PNG00	RW	RW		
PNG24	RW	RW		
PNG32	RW	RW		
PNG48	RW	RW		
PNG64	RW	RW		
PNM	RW	RW	RW	
POCKETMOD	RW			
PPM	RW	RW	RW	
PS	RW	RW		
PS2	RW			
PS3	RW			
PSB	RW			
PSD	RW	RW		
PTIF	RW	RW		

List1

PWP	R	R	
QOI	RW		
RAD	R	R	
RAF	R	R	
RAW	RW	RW	
RGB	RW	RW	
RGB565	R	RW	
RGBA	RW	RW	
RGF	RW	RW	
RLA	R	R	
RLE	R	R	R
SCT	R		
SFW	R	R	
SGI	RW	RW	
SHTML	W	W	
SID, MrSID	R	R	
SPARSE- COLOR	W	R	
SR2		R	
SRF		R	
STRIMG	RW	RW	
SUN	RW	RW	RW

List1

SVG	RW	RW	R?
TEXT	R	RW^?	RW
TGA	RW	RW	RW
TIFF	RW	RW	RW!
TIM	R	R	
TTF	R	R	
TXT	RW	RW	
UBRL	W		

List1

UBRL6	W		
UIL	W		
UYVY	RW	RW	
VICAR	RW	RW	
VIDEO	RW	?	
VIFF	RW	RW	
WBMP	RW	RW	RW
WDP	RW		
WEBP	RW	RW	RW
WMF	R	?R	
WPG	R	RW	RW
X	RW	RW	
X3F		R^	
XBM	RW	RW	RW
XCF	R	R	
XPM	RW	RW	RW

List1

XWD	RW	RW	
X3F	R	R	
YAML	W		
YCbCr	RW		
YCbCrA	RW		
YUV	RW	RW	

Hasselblad Photo RAW

Photoshop resource format

Photoshop resource text format

AAI Dune image

Animated Portable Network Graphics

Raw JPEG binary data

PFS: 1st Publisher

Sony Digital Camera Alpha Raw Image Format

Microsoft Audio/Visual Interleaved

Format derived from the keyframes of AV1 video

AVS X image

Raw blue samples

Raw mosaiced samples

Tagged Image File Format (64-bit offsets)

Better Portable Graphics

Microsoft Windows bitmap

Braille Ready Format

Continuous Acquisition and Life-cycle Support Type 1 image

Computer Graphics Metafile

Kodak Cineon Image Format

Cisco IP phone image format

Note, you must use an explicit image format specifier to read an APNG (apng:myImage.apng) image sequence, otherwise it assumes a PNG image and only reads the first frame.

Format originally used on the Macintosh (MacPaint?) and later used for PFS: 1st Publisher clip art.

Set -define dng:use-camera-wb=true to use the RAW-embedded color profile for Sony cameras. You can also set these options: use-auto-wb, no-auto-bright, and output-color.

Use **-size** and **-depth** to specify the image width, height, and depth. To specify a single precision floating-point format, use -define quantum:format=floating-point. Set the depth to 32 for single precision floats, 64 for double precision, and 16 for half-precision. For signed pixel data, use -define quantum:format=signed.

Joint Bi-level Image experts Group interchange format (JBIG-Kit 2.1 (GPL license))

Use **-quality** to specify the image compression quality. To meet the requirements of BPG, the quality argument divided by 2 (e.g. -quality 92 assigns 46 as the BPG compression).

By default the BMP format is version 4. Use BMP3 and BMP2 to write versions 3 and 2 respectively. Use -define bmp:ignore-filename to ignore the filesize check.

Uses juxtaposition of 6-dot braille patterns (thus 6x2 dot matrices) to reproduce images, using the BRF ASCII Braille encoding.

Specified in MIL-R-28002 and MIL-PRF-28002. Standard blueprint archive format as used by the US military to replace microfiche.

Requires ralcm to render CGM files.

Use **-set** to specify the image gamma or black and white points (e.g. -set gamma 1.7, -set reference-black 95, -set reference-white 685). Properties include cin:file.create_date, cin:file.create_time, cin:file.filename, cin:file.version, cin:film.count, cin:film.format, cin:film.frame_id, cin:film.frame_position, cin:film.frame_rate, cin:film.id, cin:film.offset, cin:film.prefix, cin:film.slate_info, cin:film.type, cin:image.label, cin:origination.create_date, cin:origination.create_time, cin:origination.device, cin:origination.filename, cin:origination.model, cin:origination.serial, cin:origination.x_offset, cin:origination.x_pitch, cin:origination.y_offset, cin:origination.y_pitch, cin:user.data.

List1

Raw cyan, magenta, yellow, and black samples	Use <code>-size</code> and <code>-depth</code> to specify the image width, height, and depth. To specify a single precision floating-point format, use <code>-define quantum:format=floating-point</code> . Set the depth to 32 for single precision floats, 64 for double precision, and 16 for half-precision.
Raw cyan, magenta, yellow, black, and alpha samples	Use <code>-size</code> and <code>-depth</code> to specify the image width, height, and depth. To specify a single precision floating-point format, use <code>-define quantum:format=floating-point</code> . Set the depth to 32 for single precision floats, 64 for double precision, and 16 for half-precision.
Canon Digital Camera Raw Image Format	Requires an explicit image format otherwise the image is interpreted as a TIFF image (e.g. <code>cr2:image.cr2</code>).
Canon Digital Camera Raw Image Format	A lookup table containing math instructions to replace a color (based on RGB value) by another one. It's like a color grading preset. This process is done pixel by pixel with a very high accuracy.
Microsoft Cursor Icon	Select levels like this: <code>cube:Vibrant(cube[8])</code> for level 8
DR Halo	
Digital Imaging and Communications in Medicine (DICOM) image	Used by the medical community for images like X-rays. ImageMagick sets the initial display range based on the Window Center (0028,1050) and Window Width (0028,1051) tags. Use <code>-define dcm:display-range=true</code> to set the display range to the minimum and maximum pixel values. Use <code>-define dcm:rescale=true</code> to enable interpretation of the rescale slope and intercept settings in the file. Use <code>-define dcm>window=centerXwidth</code> to override the center and width settings in the file with your own values.
Digital Camera Raw Image File <code>drawing:IMG_2600.dng</code>	Use DCRAW to leverage the raw photo decoder delegate program, e.g.,
ZSoft IBM PC multi-page Paintbrush image	Use <code>-define</code> to specify the compression (e.g. <code>-define dds:compression={dxt1, dxt5, none}</code>). Other defines include <code>dds:cluster-fit={true, false}</code> , <code>dds:weight-by-alpha={true, false}</code> , <code>dds:fast-mipmaps={true, false}</code> , and use <code>dds:mipmaps</code> to set the number of mipmaps (use fromlist to use the image list).
Microsoft Direct Draw Surface	
Raw pixel debug file, likely only useful to the developers	
Microsoft Windows Device Independent Bitmap	DIB is a BMP file without the BMP header. Used to support embedded images in compound formats like WMF.
Digital media repository	Requires the MagickCache delegate library. Supported options include <code>dmr:path</code> (location of repository), <code>dmr:passkey</code> (key to open digital media repository), <code>dmr:passphrase</code> (optionally scramble or unscramble media resource), and <code>dmr:ttl</code> (time-to-live); Set the <code>dmr:meta</code> (metadata) property to store the resource as meta data.
Digital Negative	Requires an explicit image format otherwise the image is interpreted as a TIFF image (e.g. <code>dng:image.dng</code>).
Graph Visualization	Use <code>-define</code> to specify the layout engine (e.g. <code>-define dot:layout-engine=twopi</code>).
SMPTE Digital Moving Picture Exchange 2.0 (SMPTE 268M-2003)	Use <code>-set</code> to specify the image gamma or black and white points (e.g. <code>-set gamma 1.7, -set reference-black 95, -set reference-white 685</code>).
Microsoft Enhanced Metafile (32-bit)	Only available under Microsoft Windows. Use <code>-size</code> command line option to specify the maximum width and height.

List1

Encapsulated Portable Document Format	
Adobe Encapsulated PostScript Interchange format	Requires Ghostscript to read.
Adobe Encapsulated PostScript	Requires Ghostscript to read.
Adobe Level II Encapsulated PostScript	Requires Ghostscript to read.
Adobe Level III Encapsulated PostScript	Requires Ghostscript to read.
Adobe Encapsulated PostScript	Requires Ghostscript to read.
Adobe Encapsulated PostScript Interchange format	Requires Ghostscript to read.
Adobe Encapsulated PostScript Interchange format with TIFF preview	Requires Ghostscript to read. Epson RD1 See High Dynamic-Range Images for details on this image format. To specify the output color type, use -define exr:color-type={RGB,RGBA,YC,YCA,Y,YA,R,G,B,A}. Use -sampling-factor to specify the sampling rate for YC(A) (e.g. 2x2 or 4:2:0). Requires the OpenEXR delegate library.
High dynamic-range (HDR) file format developed by Industrial Light & Magic	sRGB 16-bit RGBA lossless image format This format is a fixed width of 1728 as required by the standard. See TIFF format. Note that FAX machines use non-square pixels which are 1.5 times wider than they are tall but computer displays use square pixels so FAX images may appear to be narrow unless they are explicitly resized using a resize specification of 100x150%.
Farbfeld lossless image format	
Group 3 TIFF	
FIG graphics format	Requires TransFig.
Flexible Image Transport System	To specify a single-precision floating-point format, use -define quantum:format=floating-point. Set the depth to 64 for a double-precision floating-point format.
FilmLight floating point image format	
Free Lossless Image Format	
FlashPix Format	FlashPix has the option to store mega- and giga-pixel images at various resolutions in a single file which permits conservative bandwidth and fast reveal times when displayed within a Web browser. Requires the FlashPix SDK . Specify the FlashPix viewing parameters with the -define fpx:view.
Read and write multispectral channels as formatted text	
CompuServe Graphics Interchange Format	8-bit RGB PseudoColor with up to 256 palette entries. Specify the format GIF87 to write the older version 87a of the format. Use -transparent-color to specify the GIF transparent color (e.g. -transparent-color wheat).
Gnuplot plot files	Requires gnuplot4.0.tar.Z or later. Use -size and -depth to specify the image width, height, and depth. To specify a single precision floating-point format, use -define quantum:format=floating-point. Set the depth to 32 for single precision floats, 64 for double precision, and 16 for half-precision. For signed pixel data, use -define quantum:format=signed. ImageMagick supports scanline padding. If your image is not padded, you can instead read the image as a 1-D vector and reshape it: magick -size 38700x1 -depth 1 gray:image.bin -reshape 180x215 image.png.
Raw gray samples	

List1

Raw gray and alpha samples	Use -size and -depth to specify the image width, height, and depth. To specify a single precision floating-point format, use -define quantum:format=floating-point . Set the depth to 32 for single precision floats, 64 for double precision, and 16 for half-precision.
Radiance RGBE image format	Set the quality to 100 to produce lossless HEIC images. Requires the libheif delegate library. Recognized defines include heic:preserve-orientation={true,false}, depth-image={true,false}, heic:speed, and heic:chroma.
Apple High efficiency Image Format	HEIF is a container format supporting multiple codecs. HEIF with h.265/HEVC encoding is supported via libheif and libde265.
High Efficiency Image File Format (with h.265/HEVC encoding)	Requires hp2xx-3.4.4.tar.gz
HP-GL plotter language	
Slow Scan TeleVision	
Hypertext Markup Language with a client-side image map	Also known as HTM. Requires html2ps to read. Note, the \\xff character is not permitted in any filename when exporting client-side image maps.
Microsoft icon	Also known as ICON.
Format and characteristics of the image	
ISO/TR 11548-1 BRaiLle	Uses juxtaposition of 8-dot braille patterns (thus 8x2 dot matrices) to reproduce images, using the ISO/TR 11548-1 Braille encoding.
ISO/TR 11548-1 BRaiLle 6 dots	Uses juxtaposition of 6-dot braille patterns (thus 6x2 dot matrices) to reproduce images, using the ISO/TR 11548-1 Braille encoding.
Joint Bi-level Image experts Group file interchange format	Also known as BIE and JBG. Requires jbigkit-1.6.tar.gz .
Multiple-image Network Graphics	JPEG in a PNG-style wrapper with transparency. Requires libjpeg and libpng-1.0.11 or later, libpng-1.2.5 or later recommended.
JPEG-2000 JP2 File Format Syntax	Specify the encoding options with the -define option. See JP2 Encoding Options for more details.
JPEG-2000 Code Stream Syntax	Specify the encoding options with the -define option See JP2 Encoding Options for more details.
JPEG-2000 Code Stream Syntax	Specify the encoding options with the -define option See JP2 Encoding Options for more details.
JPEG-2000 Code Stream Syntax	Specify the encoding options with the -define option See JP2 Encoding Options for more details.
	Note, JPEG is a lossy compression. In addition, you cannot create black and white images with JPEG nor can you save transparency.
Joint Photographic Experts Group JFIF format	Requires jpegsr.v8c.tar.gz . You can set quality scaling for luminance and chrominance separately (e.g. -quality 90,70). You can optionally define the DCT method, for example to specify the float method, use -define jpeg:dct-method=float . By default we compute optimal Huffman coding tables. Specify -define jpeg:optimize-coding=false to use the default Huffman tables. Specify -define jpeg:arithmetic-coding=true to enable Huffman optimization. Two other options include -define jpeg:block-smoothing and -define jpeg:fancy-upsampling . Set the sampling factor with -define jpeg:sampling-factor . You can size the image with jpeg:size, for example -define jpeg:size=128x128 . To restrict the maximum file size, use jpeg:extent, for example -define jpeg:extent=400KB . To define one or more custom quantization tables, use -define jpeg:q-table=filename . These values are multiplied by -quality argument divided by 100.0. To avoid reading a particular associated image profile, use -define profile:skip=name (e.g. profile:skip=ICC).
JPEG extended range	Requires the jxrlib delegate library. Put the JxrDecApp and JxrEncApp applications in your execution path.

List1

JavaScript Object Notation, a lightweight data-interchange format	Include additional attributes about the image with these defines: -define json:locate, -define json:limit, -define json:moments, or -define json:features. Specify the JSON model schema version with -define json:version. The current version is 1.0. Any version less than 1.0, returns the original JSON output which included misspelled labels.
JPEG XL image coding system	Requires the JPEG XL delegate library. Use -define jxl:effort=integer to set the effort and -define jxl:decoding-speed=integer to set the decoding speed. To specify a single precision floating-point format, use -define quantum:format=floating-point. Set the depth to 32 for single precision floats and 16 for half-precision.
Kodak Photo RAW	
Kodak DC40/50/120, P850	
Morphology kernel format	format suitable for a morphology kernel
Linux reference manual pages	Requires that GNU groff and Ghostscript are installed.
MATLAB image format	
Mamiya Photo RAW	
Magick multispectral image file format	This format persists all image attributes known to ImageMagick. To specify a single precision floating-point format, use -define quantum:format=floating-point. Set the depth to 32 for single precision floats, 64 for double precision, and 16 for half-precision.
Bi-level bitmap in least-significant-byte first order	
Multiple-image Network Graphics	A PNG-like Image Format Supporting Multiple Images, Animation and Transparent JPEG. Requires libpng-1.0.11 or later, libpng-1.2.5 or later recommended. An interframe delay of 0 generates one frame with each additional layer composited on top. For motion, be sure to specify a non-zero delay.
Motion Picture Experts Group file interchange format (version 2)	Requires ffmpeg .
Motion Picture Experts Group file interchange format (version 1)	Requires ffmpeg .
Magick Pixel Cache image file format	The most efficient data processing pattern is a write-once, read-many-times pattern. The image is generated or copied from source, then various analyses are performed on the image pixels over time. MPC supports this pattern. MPC is the native in-memory ImageMagick uncompressed file format. This file format is identical to that used by ImageMagick to represent images in memory and is read by mapping the file directly into memory. The MPC format is not portable and is not suitable as an archive format. It is suitable as an intermediate format for high-performance image processing. The MPC format requires two files to support one image. Image attributes are written to a file with the extension .mpc, whereas, image pixels are written to a file with the extension .cache.
Multi-picture Object	This format permits you to write to and read images from memory. The filename is the registry key. The image persists until you explicitly delete it or the program exits. For example, let's use the MPR to create a checkerboard: magick \(\ -size 15x15 canvas:black canvas:white -append \) \ \(\ +clone -flip \) +append -write mpr:checkers +delete \ -size 240x240 tile:mpr:checkers -delete registry:checkers board.png
Magick Persistent Registry	

List1

Sony (Minolta) Raw Image File	Set <code>-define dng:use-camera-wb=true</code> to use the RAW-embedded color profile for Sony cameras.
Magick Scripting Language	MSL is the XML-based scripting language supported by the <code>conjure</code> utility. MSL requires the <code>libxml2</code> delegate library.
MTV Raytracing image format	
Magick Vector Graphics.	The native ImageMagick vector metafile format. A text file containing vector drawing commands accepted by <code>magick's -draw</code> option.
Nikon Digital SLR Camera Raw Image File	
Olympus Digital Camera Raw Image File	
open exchange format for layered raster based graphics	
On-the-air Bitmap	
Xv's Visual Schnauzer thumbnail format	
Palm pixmap	
Common 2-dimensional bitmap format	
Windows Clipboard	Only available under Microsoft Windows.
Portable bitmap format (black and white)	The maximum resolution written is 768x512 pixels since larger images require huffman compression (which is not supported). Use <code>-bordercolor</code> to specify the border color (e.g. <code>-bordercolor black</code>).
Photo CD	
Photo CD	Decode with the sRGB color tables.
HP Page Control Language	Use <code>-define</code> to specify fit to page option (e.g. <code>-define pcl:fit-to-page=true</code>).
ZSoft IBM PC Paintbrush file	
Palm Database	
ImageViewer Format	

List1

Portable Document Format	Requires Ghostscript to read. By default, ImageMagick sets the page size to the MediaBox. Some PDF files, however, have a CropBox or TrimBox that is smaller than the MediaBox and may include white space, registration or cutting marks outside the CropBox or TrimBox. To force ImageMagick to use the CropBox or TrimBox rather than the MediaBox, use -define (e.g. <code>-define pdf:use-cropbox=true</code> or <code>-define pdf:use-trimbox=true</code>). Use -density to improve the appearance of your PDF rendering (e.g. <code>-density 300x300</code>). To specify direct conversion from Postscript to PDF, use -define delegate:bimodel=true . Use -define pdf:fit-page=true to scale to the page size. To immediately stop processing upon an error, set -define pdf:stop-on-error to true. To set the page direction preferences to right-to-left, try -define pdf:page-direction=right-to-left . By default, the PDF is printed using "screen" for annotations and images. Use -define pdf:printed=true to instead utilize the printer options. Use -alpha remove to remove transparency. When writing to a PDF, thumbnails are included by default. To skip generating thumbnails, -define pdf:thumbnail=false . To enable interpolation when rendering, use -define pdf:interpolate=true .
Pentax Electronic File	Requires an explicit image format otherwise the image is interpreted as a TIFF image (e.g. <code>pef:image.pef</code>).
Embrid Embroidery Format	
Postscript Type 1 font (ASCII)	Opening as file returns a preview image.
Postscript Type 1 font (binary)	Opening as file returns a preview image.
Portable float map format	
Portable graymap format (gray scale)	
Portable float map format 16-bit half	
Personal Icon	
Apple Macintosh QuickDraw/PICT file	
Alias/Wavefront RLE image format	
Portable Network Graphics	Requires libpng-1.0.11 or later, libpng-1.2.5 or later recommended. The PNG specification does not support pixels-per-inch units, only pixels-per-centimeter. To avoid reading a particular associated image profile, use -define profile:skip=name (e.g. <code>profile:skip=ICC</code>). Set the maximum chunk size with -define png:chunk-malloc-max=value .
Portable Network Graphics	8-bit indexed with optional binary transparency

List1

Portable Network Graphics	PNG inheriting subformat from original if possible
Portable Network Graphics	opaque or binary transparent 24-bit RGB
Portable Network Graphics	opaque or transparent 32-bit RGBA
Portable Network Graphics	opaque or binary transparent 48-bit RGB
Portable Network Graphics	opaque or transparent 64-bit RGB
	PNM is a family of formats supporting portable bitmaps (PBM), graymaps (PGM), and pixmaps (PPM). There is no file format associated with pnm itself. If PNM is used as the output format specifier, then ImageMagick automagically selects the most appropriate format to represent the image. The default is to write the binary version of the formats. Use <code>-compress none</code> to write the ASCII version of the formats.
Portable anymap	Example usage: <code>magick -density 300 pages?.pdf pocketmod:organize.pdf</code>
Pocketmod personal organizer format	
Portable pixmap format (color)	Requires Ghostscript to read. To force ImageMagick to respect the crop box, use <code>-define</code> (e.g. <code>-define eps:use-cropbox=true</code>). Use <code>-density</code> to improve the appearance of your Postscript rendering (e.g. <code>-density 300x300</code>). Use <code>-alpha remove</code> to remove transparency. To specify direct conversion from PDF to Postscript, use <code>-define delegate:bimodel=true</code> .
Adobe PostScript file	
Adobe Level II PostScript file	Requires Ghostscript to read.
Adobe Level III PostScript file	Requires Ghostscript to read.
Adobe Large Document Format	Use <code>-define psd:alpha-unblend=off</code> to disable alpha blenning in the merged image. Use <code>-define psd:additional-info=all selective</code> to transfer additional information from the input PSD file to output PSD file. The 'selective' option will preserve all additional information that is not related to the geometry of the image. The 'all' option should only be used when the geometry of the image has not been changed. This option is helpful when transferring non-simple layers, such as adjustment layers from the input PSD file to the output PSD file. This define is available as of Imagemagick version 6.9.5-8. Use <code>-define psd:preserve-opacity-mask=true</code> to preserve the opacity mask of a layer and add it back to the layer when the image is saved.
Adobe Photoshop multispectral bitmap file	Multi-resolution TIFF containing successively smaller versions of the image down to the size of an icon. Use <code>-define ptif:pyramid</code> to specify the min-base and levels of the pyramid, e.g. <code>64x4</code> .
Pyramid encoded TIFF	

List1

Seattle File Works
multi-image file

Quite OK Image Format Fast, lossless image compression.

Radiance image file Requires that `ra_ppm` from the Radiance software package be installed.

Fuji CCD-RAW Graphic
File

Use `-size` and `-depth` to specify the image width, height, and depth. To specify a single precision floating-point format, use `-define quantum:format=floating-point`. Set the depth to 32 for single precision floats, 64 for double precision, and 16 for half-precision. For signed pixel data, use `-define quantum:format=signed`.

Use `-size` and `-depth` to specify the image width, height, and depth. To specify a single precision floating-point format, use `-define quantum:format=floating-point`. Set the depth to 32 for single precision floats, 64 for double precision, and 16 for half-precision.

Raw gray samples

Raw red, green, and
blue samples

Raw red, green, blue
pixels in the 5-6-5
format

Raw red, green, blue,
and alpha samples

LEGO Mindstorms EV3

Robot Graphics File

Alias/Wavefront image
file

Utah Run length
encoded image file

Scitex Continuous
Tone Picture

Seattle File Works
image

Irix RGB image

Hypertext Markup
Language client-side
image map

Used to write HTML clickable image maps based on a the output of `montage` or a format which supports tiled images such as `MIFF`.

Multiresolution
seamless image

Requires the `mrsidgeodecode` command line utility that decompresses MG2 or MG3 SID image files.

Raw text file

Format compatible with the `-sparse-color` option.
Lists only non-fully-transparent pixels.

Sony Photo RAW Sony R1

Sony Photo RAW Sony DSC-F828, Sony DSC-R1

String to images and
back

SUN Rasterfile

List1

Scalable Vector Graphics

text file

Truevision Targa image

Tagged image file multispectral format

PSX TIM file

TrueType font file
Multispectral raw text file

Unicode Braille

ImageMagick utilizes [inkscape](#) if its in your execution path otherwise [RSVG](#). If neither are available, ImageMagick reverts to its internal SVG renderer. The default resolution is 96 DPI. Use [-size](#) command line option to specify the maximum width and height. If you want to substitute entities and you trust the SVG source, enable this option: [-define svg:substitute-entities=true](#). If you want to render a very large SVG and you trust the source, enable this option: [-define svg:parse-huge=true](#).

Requires an explicit format specifier to read, e.g. `text:README.txt`.

Also known as formats ICB, VDA, and VST. Use [-define tga:preserve-orientation=true](#) to preserve the image orientation.

Also known as TIF. Requires [tiff-v3.6.1.tar.gz](#) or later. Use [-define](#) to specify the rows per strip (e.g. [-define tiff:rows-per-strip=8](#)). To define the tile geometry, use for example, [-define tiff:title-geometry=128x128](#). To specify a signed format, use [-define quantum:format=signed](#). To specify a single-precision floating-point format, use [-define quantum:format=floating-point](#). Set the depth to 64 for a double-precision floating-point format. Use [-define quantum:polarity=min-is-black](#) or [-define quantum:polarity=min-is-white](#) toggle the photometric interpretation for a bilevel image. Specify the extra samples as associated or unassociated alpha with, for example, [-define tiff:alpha=unassociated](#). Set the fill order with [-define tiff:fill-order=msb|lsb](#). Set the TIFF endianness with [-define tiff:endian=msb|lsb](#). Use [-define tiff:exif-properties=false](#) to skip reading the EXIF properties. Use [-define tiff:gps-properties=false](#) to skip reading the GPS properties. You can set a number of TIFF software attributes including document name, host computer, artist, timestamp, make, model, software, and copyright. For example, [-set tiff:software "My Company"](#). If you want to ignore certain TIFF tags, use this option: [-define tiff:ignore-tags=comma-separated-list-of-tag-IDs](#). Since version 6.9.1-4 there is support for reading photoshop layers in TIFF files, this can be disabled with [-define tiff:ignore-layers=true](#). To preserve compression of the source image, use: [-define tiff:preserve-compression=true](#).

Requires [freetype 2](#). Opening as file returns a preview image. Use [-set](#) if you do not want to hint glyph outlines after their scaling to device pixels (e.g. [-set type:hinting off](#)).

Use [-define](#) to specify the color compliance (e.g. [-define txt:compliance=css](#)).

Uses juxtaposition of 8-dot braille patterns (thus 8x2 dot matrices) to reproduce images, using the Unicode Braille encoding.

List1

Unicode BRaiLle 6 dots	Uses juxtaposition of 6-dot braille patterns (thus 6x2 dot matrices) to reproduce images, using the Unicode Braille encoding.
X-Motif UIL table	Use <code>-size</code> and <code>-depth</code> command line options to specify width and height. Use <code>-sampling-factor</code> to set the desired subsampling (e.g. <code>-sampling-factor 4:2:2</code>).
Interleaved YUV raw image	
VICAR rasterfile format	
Various video formats such as APNG, AVI, MP4, WEBM, etc. Refer to <code>defines</code> for a description of these defines: <code>video:intermediate-format</code> , <code>video:pixel-format</code> , and <code>video:vsync</code> defines, that can affect the operation on these video formats.	
Khoros Visualization Image File Format	
Wireless bitmap	Support for uncompressed monochrome only. Requires the <code>jxrlib</code> delegate library. Put the <code>JxrDecApp</code> and <code>JxrEncApp</code> applications in your execution path.
JPEG extended range	Requires the <code>WEBP</code> delegate library. The muxing delegate library is required to read animated Webp image containers. Specify the encoding options with the <code>-define</code> option See WebP Encoding Options for more details.
Weppy image format	Requires <code>libwmf</code> . By default, renders WMF files using the dimensions specified by the metafile header. Use the <code>-density</code> option to adjust the output resolution, and thereby adjust the output size. The default output resolution is 72DPI so <code>-density 144</code> results in an image twice as large as the default. Use <code>-background</code> color to specify the WMF background color (default white) or <code>-texture</code> filename to specify a background texture image.
Windows Metafile	
Word Perfect Graphics File	
display or import an image to or from an X11 server	Use <code>-define</code> to obtain the image from the root window (e.g. <code>-define x:screen=true</code>). Set <code>x:silent=true</code> to turn off the beep when importing an image.
Foveon X3 (Sigma/Polaroid) RAW	
X Windows system bitmap, black and white only	Used by the X Windows System to store monochrome icons.
GIMP image	
X Windows system pixmap	Also known as PM. Used by the X Windows System to store color icons.

List1

X Windows system window dump	Used by the X Windows System to save/display screen dumps.
Sigma Camera RAW Picture File	Include additional attributes about the image with these defines: <code>-define yaml:locate</code> , <code>-define yaml:limit</code> , <code>-define yaml:moments</code> , or <code>-define yaml:features</code> . Specify the JSON model schema version with <code>-define yaml:version</code> . The current version is 1.0.
human-readable data-serialization language	Use <code>-size</code> and <code>-depth</code> to specify the image width, height, and depth.
Raw Y, Cb, and Cr samples	Use <code>-size</code> and <code>-depth</code> to specify the image width, height, and depth.
Raw Y, Cb, Cr, and alpha samples	Use <code>-size</code> and <code>-depth</code> command line options to specify width, height, and depth. Use <code>-sampling-factor</code> to set the desired subsampling (e.g. <code>-sampling-factor 4:2:2</code>).
CCIR 601 4:1:1	